



Inspection & Rejection Machine

Anxine's pharmaceutical visual inspection machine combines precise inspection with built-in rejection systems, helping to detect and remove defective or contaminated products with speed and efficiency.

Whether you need a standalone metal detector or an integrated automated inspection and rejection system, we provide reliable solutions to support consistent quality in your pharmaceutical and nutraceutical production.

Catalogs

Tablet And Capsule Inspection Machine KPS-220B.....	1
Automatic Capsule Inspection Machine CSA-15	2



Tablet And Capsule Inspection Machine

KPS-220B



The KPS-220B is an advanced tablet and capsule inspection machine that helps manufacturers deliver products of high quality standards. The tablet visual inspection machine can identify spotted, damaged or substandard products with great accuracy. The KPS-220B machine can rotate 360 degrees, allowing for comprehensive multi-angle inspection of capsules or tablets, ensuring that each product meets production standards. Whether it is tablets, hard capsules or soft capsules, our tablet and capsule inspection machines can provide you with easy and accurate inspection solutions.

Features

- ✓ **Comprehensive Inspection:** Capable of detecting spotty, broken, or non-standard capsules and tablets.
- ✓ **360-Degree Rotation:** Ensures a full visual inspection of capsules and tablets.
- ✓ **Tablet Flipping Devise:** Allows viewing of both tablet surfaces for thorough quality checks.
- ✓ **Infinitely Adjustable Speed:** Allows precise control of rotation and inspection speeds.
- ✓ **Advanced Lighting and Mirrors:** Adjustable mirrors and lighting eliminate hidden areas, ensuring no defects are overlooked.
- ✓ **Defective Product Elimination:** Equipped with a flexible handheld vacuum nozzle for easy removal of defective products.
- ✓ **User-Friendly Design:** Simple to operate and clean, minimizing cross-contamination risks.



Technical Parameters

Model	KPS-220B
Application	Pills, capsules, tablets, soft capsules
Product Size	Minimum tablet thickness 3 mm, maximum tablet diameter 25 mm
Inspection Speed	Up to 120,000 capsules per hour or 50 kg of tablets per hour
Hopper Volume	30L or 60L
Voltage	220V 50Hz / 110V 60Hz
Weight	125 kg
Dimensions	1,400 x 650 x 1,250 mm

Automatic Capsule Inspection Machine

CSA-15



CSA-15 automatic capsule inspection machine is an intelligent quality inspection equipment designed for the pharmaceutical industry. Through advanced machine vision technology to achieve accurate detection of capsule appearance defects, CSA-15 automatic capsule inspection machine can automatically identify capsule surface and internal defects, such as insufficient filling, holes, internal gaps, cracks, etc. As China's leading capsule inspection machine supplier, our inspection equipment is not only suitable for small laboratories but also for large-scale production lines. Use our automatic capsule inspection machine to simplify the inspection process, reduce human errors, and help that every capsule meets factory standards.

Features

- ✓ **Lightweight and Sensitive:** Compact design, easy to integrate, and sensitive and stable operation
- ✓ **Advanced Defect Detection:** Automatically identifies surface and internal defects, such as insufficient filling, holes, internal chips, cracks, etc.
- ✓ **Non-Intrusive Operation:** No heat or secondary damage, preserving capsule integrity.
- ✓ **User-Friendly Maintenance:** Ensures easy on-site cleaning and maintenance, reducing downtime and costs.
- ✓ **Quiet Operation:** Provides a noise-free working environment, enhancing worker comfort.
- ✓ **Ease of Use:** Simple operation, convenient for quick training and operation.



Specifications

Model	CSA-15
Application	00#, 0#, 1#, 2#, 3#, 4#
Detectable Defects	Includes less filling, holes, internal chips, cracks, notches, short bodies, double hats, concave tops, thin spots, bubbles, and black or heterochromatic spots.
Detection Accuracy	0.5 mm
Maximum Speed	150,000 capsules per hour
Power	600 W
Operating Temperature	5°C to 35°C
Operating Humidity	10% to 80%
Dimensions	750 x 1200 x 1,420 mm
Weight	150 kg



info@anxine.com

0086 137-5776-3288

<https://www.anxine.com>

DaoHang Rd. Wenzhou, Zhejiang, China, 325200

Wenzhou Anxine Machinery Co., Ltd.