

Shrink Band Heat Tunnel CBS-1538C



Equipped with a dual-zone heating system and adjustable frame, the CBS-1538C delivers efficient tamper-evident banding and sleeve labeling for bottles and jars. This automatic shrink tunnel machine allows operators to fine-tune heat settings for different label materials and shrink zones.

Whether you're wrapping shrink bands around vitamin bottles or shrinking full-body sleeves on beverage cans, the CBS-1538C is a go-to heat shrink tunnel for companies seeking consistent shrink results. Quiet, height-adjustable, and maintenance-friendly, it's one of the most flexible heat shrink tunnels available for mid-volume labeling operations.

Features

- ✓ **Flexible Label Positioning:** Supports shrink labeling at the cap or full-body.
- ✓ **Adjustable Height:** The tunnel can be adjusted vertically to fit different product heights.
- ✓ **Heavy-Duty Build:** Durable steel structure ensures long-lasting performance.
- ✓ **Energy-Efficient Heating:** Low power use with high shrink quality.
- ✓ **Simple to Operate and Maintain:** User-friendly control panel paired with a low-maintenance design.
- ✓ **Compact Layout:** Small footprint easily fits into limited production spaces.



Specifications

Model	CBS-1538C
Tunnel Size	1,000 x 150 x 150 mm
Max Packing Size	Ø 105 x 350H mm (Adjustable)
Conveyor Motor	AC90W/220V
Conveyor Speed	0-10 m/min
Max Loading	15 kg
Shrink Film	POF, PVC, PP, PE
Power	7 kW
Power Supply	220V/50Hz
Dimension	1,500 x 350 x 1,500 mm
Weight	90 kg